




urbanTM
RESIDENTIAL
AWNING/CASEMENT WINDOW

CAPRAL
ALUMINIUM



URBAN AWNING/CASEMENT WINDOW

The Urban Awning/Casement Window has been designed to provide a clean and streamlined appearance with a modern bevelled sash profile and glazing beads. It features a continuous hook hinge system and options of either a chain winder or sash catches for ease of operation.

Full perimeter sash seals are designed to improve weather tightness and along with the option of double glazing, can provide increased thermal comfort and performance.

FEATURES AND BENEFITS

- Neat, clean appearance
- Channel and beaded sash options
- Single and double glazing options
- Lockable hardware options
- Positive sealing for improved weather performance
- Single, twin and electric winders available
- Restricted opening possible
- Integrated insect and security screening options
- Commercial perimeter frame available
- Compatible with Urban products
- Standard and tall sash options

MAXIMUM PERFORMANCE

Serviceability Pressure	2500Pa
Ultimate Pressure	3700Pa
Water Penetration	800Pa

FRAME DIMENSIONS

Option 1	48.5mm
Option 2	95.0mm

MAXIMUM RECOMMENDED SIZE

Window	Height	Width
Stay Awning *	1550mm	1210mm
Hinge Awning **	1810mm	1800mm
Casement ***	1500mm	750mm

GLAZING CAPACITY

Single Glazed	3mm-10mm
Double Glazed	12mm-18mm

WINDOW ENERGY RATINGS

Window ID	Glazing	Uw	SHGC	Tw	Air Inf
CAP-032-01	4Clr	6.6	0.65	0.67	0.08
CAP-032-03	6.38DLam	6.4	0.63	0.66	0.08
CAP-032-09	6ET	4.9	0.55	0.61	0.08
CAP-032-11	6SolT	4.9	0.43	0.47	0.08
CAP-032-10	6ETGy	4.9	0.39	0.3	0.08
CAP-034-05	4Clr/10/4Clr	4.1	0.58	0.6	0.08
CAP-034-06	4Gy/10/4Clr	4.1	0.44	0.37	0.08
CAP-034-07	4Clr/10Ar/4Clr	4.0	0.58	0.6	0.08
CAP-034-27	AGG PLUS Clr 4/10/4	3.2	0.47	0.59	0.08
CAP-034-28	AGG PLUS Clr 5/8/5	3.4	0.46	0.59	0.08
CAP-034-29	AGG PLUS Clr 6/8/4	3.4	0.46	0.59	0.08
CAP-034-30	AGG PLUS Gy 4/10/4	3.2	0.35	0.37	0.08
CAP-034-31	AGG PLUS Gy 6/8/4	3.4	0.30	0.29	0.08
CAP-034-34	AGG MAX Clr 6/8/4	3.3	0.23	0.48	0.08



Capral's Urban range is extruded in Australia using LocAl® Green primary aluminium.

- 50% lower-carbon emissions than global averages for primary aluminium
- 8kg CO₂e/kg Al
- ASI Certified Smelter



1800 ALUMINIUM (258 646)
capral.com.au
Capral Limited ABN 78 004 213 692
October 2022

View full list of Residential WERS ratings at capral.com.au